

DECLARATION DE PERFORMANCE

AF-006

1. Unique identification code of the product type: „Adera Finna”

2. **Intended use** C6 / 20/2 finishing plaster for loading, leveling and finishing of interior plasters, the recommended application thickness is minimum 1 mm, maximum 3 mm. Apply manually at a temperature of minimum 5 ° C, max. 35 ° C.

3. **Manufacturer: ETEX BUILDING PERFORMANCE SA** 98 Vulturilor Street, 5th floor, 030857, District 3, Bucharest, Romania, Phone: (+40) 31 224 01 00, Fax: (+40) 31 224 01 01 .

4. **The Performance Assessment and Verification System: SYSTEM 4**

5. **Harmonized standard:** SR EN 13279-1: 2009 “Gypsum binders and gypsum plasters”

6. **Declared performance:**

Essential characteristics	Declared performance:	Harmonized technical specification
Fire reaction	A1	SR EN 13279-1:2009
Airborne sound direct insulation	PND	
Thermal conductivity	PND	
Hazardous substances	PND	

The Declaration of Performance, Technical Data Sheet and Safety Data Sheet are available at www.siniat.ro, and the instructions for use are found on the bag.

This declaration of performance is issued in accordance with EU Regulation no. 305/2011 and EU delegated Regulation no. 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Quality Manager
Viorica Domsa



Plant Manager
Zoltan Agoston



Aghiresu Fabrici 17.05.2018